Over 30 Years of Building Quality Equipment!

HOtJelusa

DRAIN LINE JETTING EQUIPMENT

HotJet's Trailer Mounted Sewer and Drain Line Jetters are engineered for the Professional Rooter. Plumber and Municipalities and will tackle the toughest blockages! Extremely effective in removing grease, soils, ice build ups, and blockages in drain lines from 2" to 12" - Easy to operate and priced right! Our Hot Jet Units are truly versatile workhorses - and they can be utilized as a dual purpose machine. First - as a powerful drain jetter and Second as a high pressure hot water cleaning unit to clean up properties. The unit includes our Exclusive Engineering Features and the Best Warranty in the Industry!

(i.				
				ł
		-		
		DIESEL FUEL	K	/

Trailer Colors Red Black Blue

Single Engine / Gas

HOT OR COLD OPERATION CLEANS 2" TO 12" LINES

Part Number	Engine	Output*	Other Specifications
HJ2SA1040HW	35HP Vanguard or Kohler Magnum	10GPM @ 4,000 PSI	 Drive Triple V-Belt Trailer Size 5' x 10' Deck
HJ2FISA1240HW	38HP Fuel Injection Kohler Magnum	12GPM @ 4,000 PSI	 5k Rated Single Axle Popular with Universities, Hospitals & Manufacturing Plants

* Output +/- 5% PSI and GPM vary as per elevation, engine RPM and nozzle size.

Exclusive Engineering Features

Super Filter Intake System

We pre-plumb the pump intake so the draw water from the tank is dual filtered. This has proven to dramatically increase the pump life and reduce down time.

🗇 Pump

The pump systems we use are manufactured by General Pumps or Giant Pumps. These are the world's best pumps and are proven with literally thousands in service worldwide They are easy and inexpensive for service and we back them with a 10 year warranty.

Full Remote Control

Engine on/off and heater on/off for safety and convenience. Full solid state - works up to 300'.

Pump Saver System

We engineer all sewer jetter trailers with our "pump saver system" - that when the hose flow is released, the bypass water re-circulates back to the water tank. This keeps the head of the pump cool extending its life substantially.

☐ TBDS[™] (Total Belt Driven System)

All components are belt driven. The pump is Triple-V-Belt Driven. Belt driven reduces vibration and allows the pump to run at 1/2 RPM. This extends operational life, especially vs. gear driven power plants.

Chemical Application

The equipment operator can control the concentration levels at the machine and controls the chemical concentration depending on the job needs.

Dual Antifreeze Systems

(1) Our sewer jetter trailer units come with our quick antifreeze system where you close one valve and open the antifreeze ball valve - then run the machine for 30 seconds and the entire system is antifreezed. Start the machine then recapture the antifreeze in the antifreeze tank and re-attach the jetter nozzle and you are ready to jet!

(2) System Blow Out - Attach an air hose to head of pump and open all valves.

(3) Total System Recycle - In cold weather you can also leave the equipment running and it will recycle the water back to tank.



POWERFUL • BUILT TO LAST • BEST WARRANTY

This is our most popular jetter trailer package for Plumbers, Universities, Hospitals, Manufacturing Plants or any facility that requires equipment capable of tight turns and easy towing. This jetter trailer is a super combination of high PSI with great output GPM (10.0 +/-) to clean nearly any blockage in lines up to 12". Super price competitive and looks better than units that cost 2x's the price! Super dependable Vanguard Power Plant (made by a Division of Toyota) - combined with General's Premium Emperor Series Pump is a bullet proof engineering design. Add the Jumper Hose Reel for laterals and this unit becomes 2 jetters in one! With the Warthog Nozzle this unit has plenty of power to cut roots and nearly any blockage.

GENERAL SPECIFICATIONS

- 200 Gallon Water Capacity
- Molded HDP Water Tank(s)
- Adjustable Pressure Relief/Control Valve(s)
- Rear LED Lighting
- · 2" Fast Fill Pipe with 100' Fill Hose
- Full Variable Pressure and Rear Throttle Control
- · 2 PSI Gauges Front and Rear

PUMP

- General Premium TSF2021 Pump max output 10 GPM @ 4,000 PSI (+/- 5%)
- Triple V-Belt Driven for Smooth
 Operation
- Dual Safety Adjustable Blow Off Valves
- Dual Hose Pulsation Controls
- Full Ten (10) Year Warranty

MOTOR DESCRIPTION

- Engine Vanguard or Kohler Magnum 35HP, 38HP F.I.
- Battery & Battery Box
- 12 Gallon Gas Fuel Tank
- 18 Gallon Diesel Fuel Tank
- Ultra Quiet Muffler
- Three (3) Year Commercial Warranty

REMOTE CONTROL

- Solid State Remote Control Operates Equipment from Up to 300 feet
- Controls Engine On/Off and Heat On/Off
- Can be run on Manual or with the Remote control

DIESEL BURNER SYSTEM

- Heated by Diesel Fuel
- Custom engineered burn chamber for very rapid heat rise and very consistent output temperatures
- Cold rolled continuous schedule 80 coil. The horizontal coil is much easier to support for "over the road" transportation.
- Heat rise from ambient temperature @ full output is 76°

EXCLUSIVE ENGINEERING FEATURES

- Dual Antifreeze system
- Filter System
- Pump Saver System
- Soap Injection System
- TBDS (Total Belt Driven System)
- Full Recycle System

SEWER HOSE & REEL

- Sewer Hose 300' HD Steel Braided Construction - 12,000 PSI Burst - Cut Resistant
- HD Electric Single Speed Reel
- Heavy Duty 12 Volt Powered
- 120° Guide Arm with Thumb Control On/ Off

TRAILER DESCRIPTION

- · Full Premium Powder Coat
- Rugged, Specially Engineered Trailer to Haul the Equipment and Water Load
- Leaf Spring Axles Cushion and Distribute the Weight for Easy Towing
- 5'x10' Trailer
- 5k Single Axle DOT Legal in all 50 States
- Full LED Lighting

ACCESSORIES/UPGRADES AVAILABLE

- 38HP Kohler Magnum Adds \$7,495
- Tandem Axel and 330 Gl. Tank Adds \$4,995.
- Hydraulic Reel Adds \$ 3,950
- Warthog Nozzle Adds \$1,150.00

OVERALL DIMENSIONS

- Overall Length
 Deck Length
 Height
 Overall Deck Width
 Weight Dry
 2,580 lbs
- Weight Full Load
- 4,750 lbs



14773 Heritage Crest Way • Riverton, UT 84065



